




HYDRAULISET NOSTOVINSSIT



| malli | FW200 | FW200L | FW230 | FW230L | FW260 | FW300 | FW360 | FW460 |
|--|-------|--------|-------|--------|-------|-------|-------|-------|
| 1.krs voima, kN | 20 | 20 | 23 | 23 | 26 | 30 | 36 | 42 |
| viim.krs voima, kN | 14,3 | 14,3 | 16,5 | 16,5 | 18,6 | 21,2 | 25,0 | 28,0 |
| krs, n | 5 | 5 | 4 | 4 | 5 | 5 | 5 | 5 |
| vaijerin Ø, mm | 10 | 10 | 11 | 11 | 12 | 13 | 14 | 15 |
| vaijerin pituus, m | 71 | 140 | 50 | 98 | 74 | 70 | 62 | 58 |
| kiertonopeus, m/min | 25 | 25 | 24 | 24 | 30 | 29 | 28 | 26 |
| paino, kg | 86 | 98 | 87 | 100 | 120 | 129 | 136 | 140 |
| max virtaus, l/ | 50 | 50 | 50 | 50 | 65 | 65 | 65 | 65 |
| paine, bar | 160 | 160 | 175 | 175 | 170 | 175 | 180 | 190 |
| moottori, cc/rev | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 |
| moott.vääntömom., Nm | 208 | 208 | 225 | 225 | 216 | 216 | 216 | 216 |
| max vääntöm.rummulla, Nm | 2577 | 2577 | 2690 | 2690 | 5230 | 5350 | 5400 | 5453 |
| max hydr. paluupaine, bar | 2 | 2 | 2 | 2 | 2 | 2 | 2 | 2 |
| vaihteiston välityssuhde | 10,5 | 10,5 | 13,8 | 13,8 | 26,8 | 27,0 | 27,2 | 27,5 |
| paine täydessä jarruvapautuksessa, bar | 25 | 25 | 25 | 25 | 33 | 33 | 33 | 33 |

| mitat | FW200 | FW200L | FW230 | FW230L | FW260 | FW300 | FW360 | FW460 |
|---------|-------|--------|-------|--------|-------|-------|-------|-------|
| A, mm | 190 | 372 | 190 | 372 | 213 | 213 | 213 | 213 |
| B, mm | 390 | 573 | 390 | 573 | 498 | 498 | 498 | 498 |
| Ø C, mm | 220 | 220 | 220 | 220 | 250 | 250 | 250 | 250 |
| D, mm | 351 | 351 | 351 | 351 | 441 | 441 | 441 | 441 |
| E, mm | 318 | 318 | 318 | 318 | 415 | 415 | 415 | 415 |
| Ø F, mm | 320 | 320 | 320 | 320 | 400 | 400 | 400 | 400 |
| G, mm | 170 | 364 | 170 | 364 | 245 | 245 | 245 | 245 |
| H, mm | 250 | 250 | 250 | 250 | 360 | 360 | 360 | 360 |
| Ø I, mm | 15 | 15 | 15 | 15 | 19 | 19 | 19 | 19 |

Täyttää standardien EN 2006/42/CE, EN 14492-2 ja EN 12100-1-2 vaatimukset.